



Product Specifications

LF16015



Lube Filter, Spin-On

Fleetguard® LF16015 spin-on lube filter meets or exceeds OE performance requirements and the new challenges of modern engine technology.

[View product on Fleetguard.com](http://Fleetguard.com)

Specifications

Tamaño de rosca	M27X2-6H	Diámetro Exterior De La Junta	2.76 inch / 70.00 mm
Diámetro Interior De La Junta	2.46 inch / 62.60 mm	mayor diámetro exterior	3.69 inch / 93.60 mm
Longitud	6.96 inch / 176.78 mm	Tubo Vertical	No
Especificación De Prueba	ISO 4548-12	Tipo De Medio	Stratapore
Eficiencia De Partículas Primarias	30.00 micron (c) @ 97%	Flujo Nominal	21.14 gpm / 80.00 L/min

Applicable Region: North America, China, Europe, South America, South East Asia, South Pacific, Others, Mexico and Central America

Related Parts

Replaces: LF3886

"Fleetguard is a brand of Atmus Filtration Technologies ("Atmus"). This publication and all information contained or referenced in it (hereinafter "Publication") are provided as a convenience to Atmus Filtration customers "as is" without any warranties, express or implied, including warranties of merchantability, fitness for a particular purpose, or non-infringement of intellectual property. Atmus Filtration does not warrant the accuracy nor completeness of the Publication; may make changes to the Publication at any time without notice; and makes no commitment to update the Publication.

The Publication may refer to products, programs, or services that are not available in your country or local area. Consult Atmus Filtration directly for information regarding the products, programs, and services that may be available to you. Applicable law may not allow the exclusion of implied warranties, so the above exclusion may not apply to you. © 2026 Atmus Filtration Technologies Inc. All Rights Reserved